




3NA系列熔断器



选型及订货数据

选型及订货数据

	尺码号	宽度(mm)	额定电流(A)	订货号			
	00	21	6	3NA3801 2C			
			10	3NA3803 2C			
			16	3NA3805 2C			
			20	3NA3807 2C			
			25	3NA3810 2C			
			32	3NA3812 2C			
			35	3NA3814 2C			
			40	3NA3817 2C			
			50	3NA3820 2C			
			63	3NA3822 2C			
			80	3NA3824 2C			
			100	3NA3830 2C			
					30	125	3NA3832 2C
160	3NA3836 2C						
	1	30	16	3NA3105 2C			
			20	3NA3107 2C			
			25	3NA3110 2C			
			35	3NA3114 2C			
			40	3NA3117 2C			
			50	3NA3120 2C			
			63	3NA3122 2C			
			80	3NA3124 2C			
			100	3NA3130 2C			
			125	3NA3132 2C			
			160	3NA3136 2C			
					47.5	200	3NA3140
						224	3NA3142
250	3NA3144						
	2	47.5	50	3NA3220			
			63	3NA3222			
			80	3NA3224			
			100	3NA3230			
			125	3NA3232			
			160	3NA3236			
			200	3NA3240			
			224	3NA3242			
			250	3NA3244			
					57.8	300	3NA3250
						315	3NA3252
						355	3NA3254
						400	3NA3260

大豪电子
 电话: 0755-83233025
<http://www.szdahao.com>
<http://www.very-tec.com>

选型及订货数据

	尺码号	宽度(mm)	额定电流(A)	订货号
	3	57.8	200	3NA3340
			224	3NA3342
			250	3NA3344
			300	3NA3350
			315	3NA3352
		71.2	355	3NA3354
			400	3NA3360
			425	3NA3362
			500	3NA3365
			630	3NA3372
	4	101.8	630	3NA3472
			800	3NA3475
			1000	3NA3480
			1250	3NA3482
			4a	101.8
	630	3NA3672		
	800	3NA3675		
	1000	3NA3680		
	1250	3NA3682		

3NA系列熔断器

选型及订货数据

概述

NH-熔断器底座

- 用于Iso-NH-和NH-熔断器
- 符合 DIN VDE 0635、IEC269、DIN 43 620 标准
- 用于触头的绝缘罩壳是作为附件提供
- 额定电压：AC1000V/DC440V

选型及订货数据

		尺码号	导线截面至(mm ²)	额定电流(A)	订货号
	1极 扁线连接	00	95	160	3NH3030 2C
	夹持圈连接	00	6~70	160	3NH3032 2C
	3极 包括相间隔离板 扁线连接	00	95	160	3NH4030 2C
	夹持圈连接	00	6~70	160	3NH4032 2C
	1极 扁线连接	0	95	160	3NH3120
	1极 扁线连接	1	150	250	3NH3230 2C
	3极 扁线连接	1	150	250	3NH4230 2C
	1极 用于双母线连接	2	300	400	3NH3320 2C
	1极 用于双母线连接	3	2X40X5	630	3NH3530
	1极 扁线连接	4(IEC)	2X50X8	1000	3NH3530
	1极 扁线连接	4a	2X80X5	1250	3NH7520